SAFETY DATA SHEET

SECTION: 1 PRODUCT IDENTIFICATION

NOT A CONTROLLED PRODUCT

Section 8: EXPOSURE CONTROLS PERSONAL PROTECTION

Component	OSHA PEL	ACGIH TLV
Silicon Dioxide, SiO_2	(R)0.05mg/m^3	(R)0.025mg/m^3
	CAL/OSHA (R) 0.01mg/m3	
Aluminum Oxide, Al_2O_3	(T) 15mg/m^3 (R) 5mg/m^3	10mg/m^3
Ferric Oxide, Fe_2O_3	10mg/m^3	5mg/m^3
Potassium Oxide, K_2O	Not Established	Not Established
Magnesium Oxide, MgO	10mg/m^3	10mg/m^3
Carbon Dioxide, CO_2	5000ppm or 9000mg/m^3	5000ppm or 9000mg/m^3
Calcium Oxide, CaO	5mg/m^3	2mg/m^3
Sulfur, S	Not Established	Not Established
Carbon, C	Not Established	Not Established
Titanium(IV) Oxide, TiO_2	Not Established	10mg/m^3
Sodium Oxide, Na_2O	Not Established	Not Established
Magnesia, MnO	Not Established	Not Established
Water, H_2O	Not Established	Not Established

(T)= Total Dusts
(R)= Respirable Dusts

Engineering Controls: Use integral dust collection and/or exhaust ventilation, avoid inhalation of dusts. The highest probability of silica exposure occurs during installation using dry cutting methods or during removal of installed natural stone. Wet cutting methods to reduce or maintain dust levels below the PEL is highly recommended.
Skin: Wear impermeable gloves during cutting, sanding, or grinding
Eye: Wear approved Safety Goggles, or Safety Glasses and Face Shield when cutting, sanding,

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES